

Description

The 2501-2 series provide two channel operation, and each combines an AlGaAs infrared emitting diode as the emitter which is optically coupled to a silicon planar phototransistor detector in a plastic DIP8 package with different lead forming options.

With the robust coplanar double mold structure, 2501-2 series provide the most stable isolation feature.


Features

- High isolation 5000 VRMS
- DC input with transistor output
- Operating temperature range - 55 °C to 110 °C
- REACH compliance
- Halogen free (Optional)
- MSL class 1
- Regulatory Approvals
 - UL - UL1577
 - VDE - EN60747-5-5(VDE0884-5)
 - CQC - GB4943.1, GB8898
 - cUL- CSA Component Acceptance Service Notice No. 5A

Applications

- Computer peripheral interface
- Microprocessor system interface


SCHEMATIC




PIN DEFINITION

- | | |
|------------|--------------|
| 1. Anode | 8. Collector |
| 2. Cathode | 7. Emitter |
| 3. Anode | 6. Collector |
| 4. Cathode | 5. Emitter |

PACKAGE OUTLINE






ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	VALUE	UNIT	NOTE
INPUT				
Forward Current	I_F	60	mA	
Peak Forward Current	I_{FP}	1	A	1
Reverse Voltage	V_R	6	V	
Input Power Dissipation	P_i	100	mW	
OUTPUT				
Collector - Emitter Voltage	V_{CEO}	80	V	
Emitter - Collector Voltage	V_{ECO}	6	V	
Collector Current	I_C	50	mA	
Output Power Dissipation	P_O	150	mW	
COMMON				
Total Power Dissipation	P_{tot}	200	mW	
Isolation Voltage	V_{iso}	5000	V _{rms}	2
Operating Temperature	T_{opr}	-55~110	°C	
Storage Temperature	T_{stg}	-55~125	°C	
Soldering Temperature	T_{sol}	260	°C	

Note 1. 100µs pulse, 100Hz frequency


Note 2. AC For 1 Minute, R.H. = 40 ~ 60%



ELECTRICAL OPTICAL CHARACTERISTICS at Ta=25°C								
PARAMETER	SYMBOL	MIN	TYP.	MAX.	UNIT	TEST CONDITION	NOTE	
INPUT								
Forward Voltage	V _F	-	1.24	1.4	V	IF=10mA		
Reverse Current	I _R	-	-	10	μA	VR=6V		
Input Capacitance	C _{in}	-	10	-	pF	V=0, f=1kHz		
OUTPUT								
Collector Dark Current	I _{CEO}	-	-	100	nA	VCE=20V, IF=0		
Collector-Emitter Breakdown Voltage	BV _{CEO}	80	-	-	V	IC=0.1mA, IF=0		
Emitter-Collector Breakdown Voltage	BV _{ECO}	6	-	-	V	IE=0.1mA, IF=0		
TRANSFER CHARACTERISTICS								
Current Transfer Ratio	2501-2	CTR	130	-	400	%	IF=5mA, VCE=5V	
Collector-Emitter Saturation Voltage		V _{CE(sat)}	-	0.06	0.2	V	IF=20mA, IC=1mA	
Isolation Resistance		R _{ISO}	10 ¹²	10 ¹⁴	-	Ω	DC500V, 40 ~ 60% R.H.	
Floating Capacitance		C _{IO}	-	0.4	1	pF	V=0, f=1MHz	
Response Time (Rise)		t _r	-	6	18	μs	VCE=2V, IC=2mA	3
Response Time (Fall)		t _f	-	8	18	μs	RL=100Ω	3
Cut-off Frequency		f _c	-	80	-	kHz	VCE=2V, IC=2mA RL=100Ω, -3dB	4

Note 3. Fig.14

Note 4. Fig.12&13



CHARACTERISTIC CURVES

Fig.1 Forward Current vs. Ambient Temperature




Fig.2 Collector Power Dissipation vs. Ambient Temperature




Fig.3 Forward Current vs. Forward Voltage




Fig.4 Collector Dark Current vs. Ambient Temperature




Fig.5 Collector Current vs. Collector-emitter Voltage





Fig.6 Collector Current vs. Collector-emitter Voltage



CHARACTERISTIC CURVES

Fig.7 Normalized Current Transfer Ratio vs. Forward Current




Fig.8 Normalized Current Transfer Ratio vs. Ambient Temperature




Fig.9 Collector-emitter Saturation Voltage vs. Ambient Temperature




Fig.10 Switching Time vs. Load Resistance





Fig.11 Frequency Response



TEST CIRCUITS

Fig.12 Test Circuits of Response Time




Fig.13 Curves of Response Time







Fig.14 Test Circuits of Frequency Response







PACKAGE DIMENSIONS (Dimensions in mm unless otherwise stated)

Standard DIP – Through Hole (DIP Type)




Gullwing (400mil) Lead Forming – Through Hole (M Type)







PACKAGE DIMENSIONS (Dimensions in mm unless otherwise stated)

Surface Mount Lead Forming (S Type)




Surface Mount (Low Profile) Lead Forming (SL Type)






RECOMMENDED SOLDER MASK (Dimensions in mm unless otherwise stated)


Surface Mount Lead Forming & Surface Mount (Low Profile) Lead Forming







Carrier Tape Specifications (Dimensions in mm unless otherwise stated)

Option S(T1) & SL(T1)




Option S(T2) & SL(T2)





REEL SPECIFICATIONS (Dimensions in mm unless otherwise stated)

Option S & Option SL



BOX SPECIFICATIONS (Reel Type)

Inner Box

- L x W x H = 36cm x 36cm x 6.9cm

Outer Box

ORDERING AND MARKING INFORMATION

MARKING INFORMATION



PS : Series Abbr.
2501-2 : Part Number
Y : Fiscal Year
WW : Work Week
EE : Manufacturing Code

ORDERING INFORMATION


LABEL INFORMATION

PS2501-2L(Z)

PS – Series Abbr.
 2501-2 – Part Number
 L – Lead Form Option (SM/S/SL/None)
 Z – Tape and Reel Option (T/R1 or T/R2)


PACKING QUANTITY

Option	Quantity	Quantity – Inner box	Quantity – Outer box
None	50 Units/Tube	16 Tubes/Inner box	10 Inner box/Outer box = 8k Units
SM	50 Units/Tube	16 Tubes/Inner box	10 Inner box/Outer box = 8k Units
SMT/R1	1000 Units/Reel	2 Reels/Inner box	5 Inner box/Outer box = 10k Units
SMT/R2	1000 Units/Reel	2 Reels/Inner box	5 Inner box/Outer box = 10k Units
SLT/R1	1000 Units/Reel	2 Reels/Inner box	5 Inner box/Outer box = 10k Units
SLT/R2	1000 Units/Reel	2 Reels/Inner box	5 Inner box/Outer box = 10k Units




REFLOW INFORMATION

REFLOW PROFILE




Profile Feature	Sn-Pb Assembly Profile	Pb-Free Assembly Profile
Temperature Min. (T Amin)	100	150°C
Temperature Max. (T smax)	150	200°C
Time (ts) from (T Amin to T smax)	60-120 seconds	60-120 seconds
Ramp-up Rate (tL to tP)	3°C/second max.	3°C/second max.
Liquidous Temperature (TL)	183°C	217°C
Time (tL) Maintained Above (TL)	60 – 150 seconds	60 – 150 seconds
Peak Body Package Temperature	235°C +0°C / -5°C	260°C +0°C / -5°C
Time (tP) within 5°C of 260°C	20 seconds	30 seconds
Ramp-down Rate (TP to TL)	6°C/second max	6°C/second max
Time 25°C to Peak Temperature	6 minutes max.	8 minutes max.



TEMPERATURE PROFILE OF SOLDERING

WAVE SOLDERING (JESD22-A111 COMPLIANT)



HAND SOLDERING BY SOLDERING IRON

Soldering Temperature	380+0/-5°C
Soldering Time	3 sec max.

- One time soldering is recommended for all soldering method.
- Do not solder more than three times for IR reflow soldering.

DISCLAIMER

- ASG is continually improving the quality, reliability, function and design. ASG reserves the right to make changes without further notices.
- The characteristic curves shown in this datasheet are representing typical performance which are not guaranteed.
- ASG makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, ASG disclaims (a) any and all liability arising out of the application or use of any product, (b) any and all liability, including without limitation special, consequential or incidental damages, and (c) any and all implied warranties, including warranties of fitness for particular
- The products shown in this publication are designed for the general use in electronic applications such as office automation, equipment, communications devices, audio/visual equipment, electrical application and instrumentation purpose, non-infringement and merchantability.
- This product is not intended to be used for military, aircraft, automotive, medical, life sustaining or lifesaving applications or any other application which can result in human injury or death.
- Please contact ASG sales agent for special application request.
- Immerge unit's body in solder paste is not recommended.
- Parameters provided in datasheets may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated in each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify ASG's terms and conditions of purchase, including but not limited to the warranty expressed therein.
- Discoloration might be occurred on the package surface after soldering, reflow or long-time use. It neither impacts the performance nor reliability.